

## Seat Belts for Forklift

Forklift Seat Belts - Described in the Regulation guidelines are the use of seatbelts and operator restraints on forklifts. It states that the accountability falls on the employers' to be able to make sure that every machine, piece of equipment and device is utilized properly used in accordance to the instructions of the producer.

Rough Terrain lift trucks ought to meet the guidelines of ANSI Standard ASME B56.6-1992 regarding their fabrication, use, design, maintenance and inspection.

Mobile equipment like side boom tractors with a Rollover Protective Structure (ROPS), must have seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile equipment has seat belts required by law, the operator and subsequent passengers should ensure they make use of the belts whenever the motor vehicle is in motion or engaged in operation since this could cause the equipment to become unsteady and thus, unsafe.

If a seat belt or other driver restraint is required on a forklift.

While working a lift truck, the seat belt requirements would depend on some factors. Contributing factors to this determination might include whether the the lift truck is outfitted along with a Rollover Protective Structure, the type of lift truck itself and the year the lift truck was actually manufactured. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial forklifts, ANSI Standard ASME B56.1-1993 refers to a driver restraint device, enclosure or system. A driver restraint device, system, or enclosure is intended so as to aid the operator in lessening the possibility of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device might comprise a seat belt, although a seat belt is not essentially a part of such equipment or system.